

INSTALLER FRIENDLY SERIES® - IFS Three Phase Duplex

Three phase, duplex demand dose or timed dose, float or C-Level™ sensor controlled system for pump control and system monitoring.

The IFS duplex control panel is designed to control two (alternating) 208, 240 or 480 VAC three phase pumps in water and sewage installations. The alternating action equalizes pump wear. In addition to the alternating pump control, this system provides override control should either pump fail.

The panel features an easy-to-use touch pad with display on the inner door for programming and system monitoring. The panel configuration can be easily converted in the field to either a timed dose or demand dose.

The optional C-Level™ sensor is a pressure transducer that senses the liquid level in the tank and sends a signal to the IFS panel. Pump activation levels can be adjusted by using the panel touch pad. C-Level™ CL40 sensor operating range is 3-39.9 inches (7.6-101.3 cm). C-Level™ CL100 operating range is 3-99.5 inches (7.6-252.7 cm).

TOUCH PAD FEATURES



- A. **Level Status Indicators** illuminate when floats or set points are activated. Alarm will activate if a float operates out of sequence.
- B. **HOA (Hand-Off-Automatic) Buttons** control pump mode with indication. Hand mode defaults to Automatic when stop level or redundant off level is reached.
- C. **Pump Run Indicators** will illuminate when pumps are called to run.
- D. **Lead/Lag Selector** toggles pump operation (alternate 1-2 and 2-1).
- E. **LED Display** shows system information including: level in inches or centimeters (C-Level™ only), mode, pumps elapsed time (hh:mm), events (cycles), alarm counter, float error count, timed dose override counter (timed dose only), and ON/OFF times (timed dose only).
- F. **NEXT Push Button** toggles display.
- G. **UP and SET Push Buttons** set pump ON/OFF times (timed dose only) and activation levels (C-Level™ only).

PANEL COMPONENTS

1. **Enclosure** base measures 16 X 14 X 6 inches (40.64 X 35.56 X 15.24 cm). NEMA 4X (ultraviolet stabilized thermoplastic with removable mounting feet for outdoor or indoor use). **Note:** Options, voltage, and amp range selected may change enclosure size and component layout.
2. **Red Alarm Beacon** provides 360° visual check of alarm condition.
3. **Exterior Alarm Test/Normal/Silence Switch** allows horn and light to be tested and horn to be silenced in an alarm condition. Alarm automatically resets once alarm condition is cleared.
4. **Alarm Horn** provides audio warning of alarm condition (83 to 85 decibel rating).
5. **Motor Protective Switches** provide adjustable overload, branch circuit protection and pump disconnect.
6. **IEC Motor Contactors** control pumps by switching electrical lines.
7. **Multi-Tap Transformer** (208/240/480 VAC primary) provides 120V control alarm voltage or 600VAC primary transformer.
8. **Float Connection Terminal Block**
9. **Control Power Indicator/Fuse** indicator light illuminates if control power is present in panel. Alarm activates if control fuse is blown.
10. **Alarm Power Indicator/Fuse** indicator light illuminates if alarm power is present in panel.
11. **Large Incoming Power Connection Terminal Block**
12. **Terminal Block Float Wiring Label**
13. **Ground Lugs**

NOTE: Schematic/Wiring Diagram and Pump Specification Label are located inside the panel on enclosure cover

SEE BACKSIDE FOR COMPLETE LISTING OF AVAILABLE OPTIONS.



Model Shown IFS61W001X8AC

Reg. Cdn Pat. & TM Off

C-Level™ Sensor US Patent No. 8,336,385; 8,567,242; 8,650,949

FEATURES

- Entire control system is UL Listed to meet and/or exceed industry safety standards
- Dual safety certification for the United States and Canada
- Standard package includes three 20' SJE MilliAmpMaster™ control switches
- Complete with step-by-step installation instructions
- Five-year limited warranty



SJE Rhombus

PO Box 1708, Detroit Lakes, MN 56502

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: customer.service@sjerhombus.com

www.sjerhombus.com B.17

IFS6 **1** **W** **8AC**

MODEL IFS6 \$2195.00

ALARM PACKAGE
 1 = alarm package (includes test/normal/silence switch, fuse, red light, horn, & float) Base

ENCLOSURE RATING
 W = Weatherproof, NEMA 4X (engineered thermoplastic) Base

PUMP FULL LOAD AMPS

208/240/480V	600V	
<input type="checkbox"/> 001 = 1.0-1.6 FLA	<input type="checkbox"/> 005 = 1.0-1.6 FLA	Base
<input type="checkbox"/> 101 = 1.6-2.5 FLA	<input type="checkbox"/> 105 = 1.6-2.5 FLA	Base
<input type="checkbox"/> 201 = 2.5-4.0 FLA	<input type="checkbox"/> 205 = 2.5-4.0 FLA	Base
<input type="checkbox"/> 301 = 4.0-6.3 FLA	<input type="checkbox"/> 305 = 4.0-6.3 FLA	Base
<input type="checkbox"/> 401 = 6.0-10.0 FLA	<input type="checkbox"/> 405 = 6.0-10.0 FLA	Base
<input type="checkbox"/> 511 = 9.0-14.0 FLA	<input type="checkbox"/> 515 = 9.0-14.0 FLA	\$60.00
<input type="checkbox"/> 611 = 13.0-18.0 FLA	<input type="checkbox"/> 615 = 13.0-18.0 FLA	\$60.00
<input type="checkbox"/> 621 = 17.0-23.0 FLA	<input type="checkbox"/> 625 = 17.0-23.0 FLA	\$80.00
<input type="checkbox"/> 701 = 20.0-25.0 FLA	<input type="checkbox"/> 705 = 20.0-25.0 FLA	\$80.00

FLOAT SWITCH APPLICATION

H = pump down (select 17 option) Base

X = no floats \$75.00

C = C-Level™ sensor (must select 24 or 29 option) \$75.00
 (select option 3E and/or 4A & 4D for high water alarm and/or redundant off floats)

Note: Pump down applications only.
Industry practices suggest that a secondary device, such as a float switch, be used for redundant activation of the high level alarm and pump shut off.

OPTIONS Listed below

ENCLOSURE UPSIZE - If you selected one or more of the options, add a one-time \$50.00 list enclosure upsize

Total Options _____
Enclosure Upsize _____
TOTAL LIST PRICE _____

CODE	DESCRIPTION	LIST PRICE	CODE	DESCRIPTION	LIST PRICE
<input type="checkbox"/> 3A	Alarm flasher	\$50.00	<input type="checkbox"/> 16A	10' cord in lieu of 20' (per float)	\$2.00
<input type="checkbox"/> 3B	Manual alarm reset	\$90.00	<input type="checkbox"/> 16B	15' cord in lieu of 20' (per float)	\$1.00
<input type="checkbox"/> 3E	High water alarm float (must select 17 option)	\$25.00	<input type="checkbox"/> 16C	30' cord in lieu of 20' (per float)	\$5.00
(Available only when Switch Applications = C)			<input type="checkbox"/> 16D	40' cord in lieu of 20' (per float)	\$15.00
<input type="checkbox"/> 4A	Redundant off	\$55.00	<input type="checkbox"/> 17C	Sensor Float® / internally weighted ▲ (per float)	\$5.00
(select option 4D if floats are required)			<input type="checkbox"/> 17D	Sensor Float® / externally weighted ▲ (per float)	\$7.00
<input type="checkbox"/> 4D	Redundant off float		<input type="checkbox"/> 17G	SJE MilliAmpMaster™ / pipe clamp ● (per float)	\$0.00
(must select 4A option) (must select 17 option)		\$25.00	<input type="checkbox"/> 17H	SJE MilliAmpMaster™ / externally weighted ● (per float)	\$7.00
<input type="checkbox"/> ★ 5A	Thermal cutout/heat sensor auto reset	\$80.00	<input type="checkbox"/> 17J	Sensor Float® / pipe clamp ▲ (per float)	\$0.00
(for pumps w/thermal switch leads)			<input type="checkbox"/> 19F	Fourth float to separate alarm function from lag	\$25.00
<input type="checkbox"/> ★ 5E	Seal failure circuit & red indicator (2 wire)	\$315.00	<input type="checkbox"/> 24E	C-Level™ CL40 sensor with 4' vent tube & 20' cord	\$280.00
<input type="checkbox"/> 6A	Auxiliary alarm contacts, form C	\$40.00	<input type="checkbox"/> 24F	C-Level™ CL40 sensor with 4' vent tube & 40' cord	\$310.00
<input checked="" type="checkbox"/> 8AC	Display board includes: ETM counter, events (cycles) counter, alarm counter and lead/lag selector switch. (Included as standard)	\$0.00	<input type="checkbox"/> 24G	C-Level™ CL40 sensor with 8' vent tube & 20' cord	\$285.00
<input type="checkbox"/> 10E	Lockable latch - NEMA 4X	\$40.00	<input type="checkbox"/> 24H	C-Level™ CL40 sensor with 8' vent tube & 40' cord	\$315.00
<input type="checkbox"/> 10G	Lightning arrester	\$200.00	<input type="checkbox"/> 24X	No C-Level™ CL40 sensor	\$0.00
<input type="checkbox"/> 10K	Anti-condensation heater	\$100.00	<input type="checkbox"/> 29A	C-Level™ CL100 sensor w/10' vent tube & 20' cord	\$290.00
<input type="checkbox"/> 11C	NEMA 1 remote alarm panel (must select option 6A)	\$80.00	<input type="checkbox"/> 29B	C-Level™ CL100 sensor w/10' vent tube & 40' cord	\$320.00
<input type="checkbox"/> 11D	NEMA 4X remote alarm panel (must select option 6A)	\$250.00	<input type="checkbox"/> 29X	No C-Level™ CL100 sensor	\$0.00

● Mechanically-activated ▲ Mercury-activated

If additional features are required, call the factory for a quote on an Engineered Custom control panel.

SAMPLE

MODEL	IFS 6 1 W 001 H 8AC 10E 17G	IFS6 \$2195.00
Model Type		1 Base
Alarm Package		W Base
Enclosure Rating		001 Base
Pump Full Load Amps		H Base
Switch Application		8AC \$100.00
Options: Display, Lockable Latch, SJE MilliAmpMaster™/pipe clamp		10E \$40.00
		17G \$0.00
		TOTAL LIST PRICE \$2335.00