

SENSOR FLOAT® Control Switch

Mercury-activated, narrow-angle float switch designed to activate pump control panels and alarms.

This narrow-angle sensing device is used to accurately monitor liquid levels in sewage and non-potable water applications. The Sensor Float® control switch is not sensitive to rotation and is suitable for use with intrinsically safe circuits. Contact SJE-Rhombus regarding specific intrinsically safe applications.

Normally Open Model (high level)

The control switch turns on (closes) when the switch tips slightly **above** horizontal signaling a high level, and turns off (opens) when the switch drops slightly below horizontal.

Normally Closed Model (low level)

The control switch turns on (closes) when the switch drops slightly **below** horizontal signaling a low level, and turns off (opens) when the switch tips slightly above horizontal.



FEATURES

- Suitable for use with intrinsically safe circuits.
- Not sensitive to rotation.
- Control differential of .5 inches (1 cm) above or below horizontal.
- UL Listed for use in non-potable water and sewage.
- CSA Certified.
- Five-year limited warranty.



SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL,CSA) SJOW, water-resistant (CPE)

FLOAT: 3.38 inch diameter x 4.55 inch long (8.58 cm x 11.56 cm), high-impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 PSI (90 kPa)

MERCURY TILT SWITCH: single pole, single throw, mercury-to-mercury contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp, 120/230 VAC, 50/60 Hz

OPTIONS

This switch is available:

- for normally open (high level) applications or normally closed (low level) applications.
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters (longer lengths available).
- with three mounting options that allow for flexibility in installation:

Mounting Clamp: for applications where the switch can be attached to a discharge pipe or similar mounting device.

Internally Weighted: for applications where the switch can be suspended from above.

Externally Weighted: for applications where the switch can be suspended from above.



SJE RHOMBUS

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax

email: customer.service@sjerhombus.com

www.sjerhombus.com G.15

SEE BACKSIDE FOR ORDERING INFORMATION.

SENSOR FLOAT® Control Switch

Mercury-activated, narrow-angle float switch designed to activate pump control panels and alarms.

ORDERING INFORMATION

Normally Open		Normally Closed		List Price	Shipping Weight
Part#	Description	Part#	Description		
1002108	10PCNO	1002111	10PCNC	\$49.88	1.29 lbs.
1002072	10SWINO	1002075	10SWINC	\$53.85	1.85 lbs.
1002143	10SWENO	1002146	10SWENC	\$59.81	2.66 lbs.
1002117	15PCNO	1002120	15PCNC	\$54.01	1.64 lbs.
1002080	15SWINO	1002083	15SWINC	\$58.00	2.22 lbs.
1002152	15SWENO	1002155	15SWENC	\$63.97	2.90 lbs.
1002125	20PCNO	1002128	20PCNC	\$58.17	1.99 lbs.
1002089	20SWINO	1002092	20SWINC	\$62.19	2.59 lbs.
1002161	20SWENO	1002164	20SWENC	\$68.14	3.27 lbs.
1002134	30PCNO	1002137	30PCNC	\$67.26	2.13 lbs.
1002098	30SWINO	1002101	30SWINC	\$71.22	3.28 lbs.
1002170	30SWENO	1002173	30SWENC	\$77.18	3.88 lbs.

PC = Pipe Clamp WI = Weighted Internally WE = Weighted Externally

NO = Normally Open NC = Normally Closed

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30).

OPTIONS

PACKAGING

Bagged - standard

Boxed - optional

Bulk - optional

ADDITIONAL CABLE

Longer cable lengths available. Please call for details.

UL Listed for
Water & Sewage



SPECIFICATIONS

CABLE: flexible 18 gauge, 2 conductor (UL, CSA) SJOW, water-resistant (CPE) jacket

FLOAT: 3.38 inch diameter x 4.55 inch long (8.58 cm x 11.56 cm), high impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 140°F (60°C)

MAXIMUM WATER DEPTH: 30 feet (9 meters), 13 psi

MERCURY SWITCH: single pole, single throw, mercury-to-mercury contacts, hermetically sealed in a steel capsule and epoxy sealed in the float housing

ELECTRICAL: 5 amp 120-/230 VAC, 50/60 Hz

NOTE: Suitable for use with intrinsically safe circuits

Contact SJE-Rhombus regarding specific intrinsically safe applications.

OTHER INFORMATION

NORMALLY OPEN (HIGH LEVEL) OPERATION

The control switch closes (turns on) when the float tips slightly **above** horizontal signaling a high level, and opens (turns off) when the float drops slightly **below** normal.

NORMALLY CLOSED (LOW LEVEL) OPERATION

The control switch closes (turns on) when the float drops slightly **below** horizontal signaling a low level, and opens (turns off) when the float tips slightly **above** horizontal.



SJE RHOMBUS

www.sjerhombus.com

customer.service@sjerhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617

Product offering and pricing are subject to change without notice.

Please visit www.sjerhombus.com for the most current information.