

FLOAT ACCESSORIES

Cable Clamp Assembly, Float Brackets, Pipe Mounting Bracket,
Cable Weights, ETM w/ Piggy-Back Plug, Vertical Reed Switch, Anchor and Chain

CABLE WEIGHT

Provides an accurate pivot point for suspended float switches.

- Gripper teeth on clip and weight channel securely lock float cable into place
- Cable Weight can be adjusted without the use of tools



U.S. Patent 5,306,885

HOUSING: 1 pound, 5 ounce (0.6 kgs.), 2.8 inch diameter x 3.3 inch long (7.1 cm diameter x 8.4 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C).

CLIP: injection molded acetal plastic

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3

SHIP WEIGHT: 1.6 lbs. (.726 kgs)

Part Number	Description
1002230	Cable Weight

CABLE WEIGHT MINI

Provides an accurate pivot point for suspended float switches.

- One piece cable weight
- Turn and Lock for easy installation.



HOUSING: 9.6 ounces (0.27 kgs.), 2.5 inch diameter x 2.5 inch long (6.35 cm diameter x 6.35 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C)

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3

Part Number	Description
1030356	Cable Weight Mini

ELAPSED TIME METER WITH PIGGY-BACK PLUG

Plugs into switched outlet or piggy-back switch of plugger control panel. Unit must be placed inside an enclosure.

- Screws and mounting adhesive included.



Part Number	Description
1022846	ETM w/120V piggy-back plug
1032834	ETM w/230V piggy-back plug

VERTICAL REED SWITCH

- Control differential: .375 inch (1 cm)
- Maximum angle from vertical: 5°
- Electrical: 250 mAmps, 12-125 VAC, 50/60 Hz
500 mAmps, 6-12 VDC, 50/60 Hz
- Housing and Float: 1.60 inch diameter x 6.7 inch long (4.06 cm X 17.01 cm), high impact, corrosion resistant PVC for use in sewage and non-potable water up to 120°F (50°C)



Part Number	Description
1011027	10ft VRS 120V Bulk
1016561	15ft VRS 120V Bulk

ANCHOR

- 10 lb. weight
- Yellow, vinyl coated, mushroom style



Part Number	Description
1018687	10 lb. Mushroom Anchor

CHAIN

- 1/8" thickness
- 316 grade stainless steel
- Available in one foot increments



Part Number	Description
1018823	1/8 inch Chain

PRODUCTS CONTINUED ON NEXT PAGE.
SEE PRICE BOOK FOR LIST PRICES.



SJE RHOMBUS

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: customer.service@sjerhombus.com

www.sjerhombus.com H.7

FLOAT ACCESSORIES

Cable Clamp Assembly, Float Brackets, Pipe Mounting Bracket,
Cable Weights, ETM w/ Piggy-Back Plug, Vertical Reed Switch, Anchor and Chain

CABLE CLAMP ASSEMBLY

Provides cable anchor point and strain relief. Secures cable in vertical direction.


- For use with 18/16 gauge, 14 gauge, & 12 gauge cable
- Mounting clamp: ABS Nylon blend
- Hose clamp: highly corrosion resistant stainless steel



Part Number	Description
1008569	18 & 16 Gauge Cable Clamp Assembly
1008574	14 Gauge Cable Clamp Assembly
1008575	12 Gauge Cable Clamp Assembly

PIPE MOUNTING BRACKET

- Secures discharge pipe to basin wall.
- Clamps directly to 2" PVC discharge pipe.




Part Number	Description
1027771	Pipe Mounting Bracket

FLOAT BRACKET

Provides convenient installation of float switches.

- Six Float Bracket supports 1-6 floats
- Four Float Bracket supports 1-4 floats
- Can be directly mounted to wall or used with wall mounting device
- Provides convenient location to stow excess float cord
- Supplied with UL Recognized cord strain relief connectors



METAL COMPONENTS: all metal components are made of 300 series stainless steel

STRAIN RELIEF CONNECTORS: which accommodate 18/2, 18/3, 16/2, 16/3 SJOW and SJTW cords

Part Number	Description
1009432	4 Float Bracket With Mounting Device
1009433	4 Float Bracket Without Mounting Device
1009434	6 Float Bracket With Mounting Device
1009435	6 Float Bracket Without Mounting Device
1009436	Float Bracket Mounting Device

www.sjerhombus.com
customer.service@sjerhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617

Product offering and pricing are subject to change without notice.
Please visit www.sjerhombus.com for the most current information.