

SJE PUMPMASTER® WPS Float Switch

Mechanically-activated, wide-angle switch designed for direct control of pumps up to 1/2 HP at 120 VAC and 1 HP at 230 VAC or control applications as low as 120 VAC, 100 mA.

This mechanically-activated, wide-angle float switch provides automatic control in:

- potable water applications
- water applications

It can be wired to work in either pump down (normally open) or pump up (normally closed) applications.

The SJE PumpMaster® WPS float switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.



FEATURES

- Can be wired to work in either pump down (normally open) or pump up (normally closed) applications (**Single Pole, Double Throw**).
- Heavy-duty contacts.
- Controls pumps up to 1/2 HP at 120 VAC and 1 HP at 230 VAC or control applications as low as 120 VAC, 100 mA
- For direct wiring applications.
- Adjustable pumping range of 7 to 36 inches (18 to 91 cm).
- Includes external cable weight and boxed packaging.
- CSA Certified to meet NSF/ANSI 61 standard for use in potable water. Approved for use in tanks of 250 US gallons (950L) in volume or greater per float.
- Five-year limited warranty.



SPECIFICATIONS

CABLE: flexible 16 gauge, 3 conductor (UL, CSA) SJOW, water-resistant (CPE)

FLOAT: 3.05 inch diameter x 3.56 inch long (7.75 x 9.04 cm) high impact, corrosion resistant, PVC housing for use in potable water and water up to 140°F (60°C)

ELECTRICAL:
120/230 VAC 50/60 Hz
13 FLA, 85 LRA

NOTE: This switch must be used with pumps that provide integral thermal overload protection.

Minimum Electrical Load:
120 VAC, 100 mA

NOTE: This switch is not intended to control non-arcing loads.

SEE BACKSIDE FOR ORDERING INFORMATION.


SJE RHOMBUS

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax
email: customer.service@sjerhombus.com



www.sjerhombus.com

F.1

SJE PUMPMASTER® WPS Float Switch

Mechanically-activated, wide-angle switch designed for direct control of pumps up to 1/2 HP at 120 VAC and 1 HP at 230 VAC or control applications as low as 120 VAC, 100 mA.

ORDERING INFORMATION

PUMP DOWN OR PUMP UP  		Shipping Weight
Part Number	Description	
1047427	15PMWPSWE	3.3 lbs.
1053697	30PMWPSWE	5.1 lbs.

WE = Weighted Externally

Can be wired to work in either pump down (normally open) or pump up (normally closed) applications (Single Pole, Double Throw).

OPTIONS

EXTERNAL WEIGHT
is standard

PACKAGING
Boxed - standard



SPECIFICATIONS

CABLE: flexible 16 gauge, 3 conductor
(UL, CSA) SJOW, water-resistant (CPE)

FLOAT: 3.05 inch diameter x 3.56 inch long
(7.75 x 9.04 cm) high impact, corrosion resistant, PVC housing for use in potable water and water up to 140°F (60°C)

ELECTRICAL:

120/230 VAC 50/60 Hz
13 FLA, 85 LRA

NOTE: This switch must be used with pumps that provide integral thermal overload protection.

Minimum Electrical Load:

120 VAC, 100 mA

NOTE: This switch is not intended to control non-arcing loads.

OTHER INFORMATION

PUMP DOWN is normally open contacts for emptying applications.

PUMP UP is normally closed contacts for filling applications.

Call or fax your order!
1-888-DIAL-SJE (1-888-342-5753) / Fax 218-847-4617

*Product offering and pricing are subject to change without notice.
Please visit www.sjerhombus.com for the most current information.*


SJE RHOMBUS
www.sjerhombus.com
customer.service@sjerhombus.com