

MODEL PS11/PS12 Control Panel


Single phase, two independant motor contactor control/programmable timed dosing control panel.

The PS11 (120V) PS12 (240V) control panel provide a reliable means of controlling **both** pump chamber and sand filter pumps in an onsite septic installation.

PANEL COMPONENTS

1. **Enclosure** measures 14 x 12 x 6 inches (35.56 x 30.48 x 15.24 cm); NEMA 4X (ultraviolet stabilized thermoplastic) with removable mounting feet for indoor or outdoor use.
2. **Pump Chamber Magnetic Motor Contactor** controls pump chamber pump by switching electrical lines.
3. **Sand Filter Magnetic Motor Contactor** controls sand filter pump by switching electrical lines.
4. **Alarm/Control Fuse**
5. **Float Switch Terminal Block**
6. **Control/Pump Power Terminal Block**
7. **Programmable Timer** features separate variable controls to allow for pump chamber pump on/off time settings from .05 seconds to 30 hours.
8. **Pump Chamber Circuit Breaker** provides pump chamber disconnect and provides branch circuit protection.
9. **Sand Filter Circuit Breaker** provides sand filter pump disconnect and provides branch circuit protection.
10. **HOA Switches** provide manual pump control.
11. **Ground Lugs**
12. **Spare Fuse**
13. **Red Alarm Beacon** provides 360° visual check of alarm condition.
14. **Alarm Horn** provides audio warning of alarm condition (83 to 85 decibel rating).
15. **Exterior Alarm Test/Normal/Silence Switch** allows horn and light to be tested and horn to be silenced in an alarm condition. Alarm automatically resets once alarm condition is cleared.
16. **Horn Silence Relay** (mounted under bracket).
17. **Elapsed Time Meter**
18. **Event Counter**

NOTE: Wiring Diagram, Pump Specification Label and Timer Installation Label are located inside the panel on enclosure cover.



Model Shown PS12



FEATURES

- Entire control system (panel and switches) is UL Listed to meet and/or exceed industry safety standards
- Dual safety certification for the United States and Canada
- Standard package includes three 20' SJE PumpMaster® pump switches, and one 20' SJE PumpMaster® SPDT pump switch
- Complete with step-by-step installation instructions
- Five-year limited warranty

SEE BACKSIDE FOR COMPLETE LISTING OF AVAILABLE OPTIONS.
SEE PRICE BOOK FOR LIST PRICE.



SJE RHOMBUS

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax

email: customer.service@sjerrhombus.com

www.sjerrhombus.com **B.63**

MODEL PS11/PS12 Onsite Control Panel

Single phase, two independent motor contactor control/programmable timed dosing control panel.

120 VAC		List Price	Shipping Weight
Part #	Description		
1006586	PS11	\$1,282.00	26 lbs.

Shipping

240 VAC		List Price	Shipping Weight
Part #	Description		
1007395	PS12	\$1,641.00	26 lbs.

SEE PRICE BOOK FOR LIST PRICE.



SPECIFICATIONS

VOLTAGE: 120 VAC (PS11) or 240 VAC (PS12)

ENCLOSURE: 14 x 10 x 6 inch (35.56 x 30.48 x 15.24 cm)
NEMA 4X weatherproof thermoplastic with hinged door.

BRANCH CIRCUIT PROTECTION: Circuit breakers for pump chamber and sand filter pumps.



SJE RHOMBUS

www.sjrhombus.com
customer.service@sjrhombus.com

Call or fax your order!
1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617

*Product offering and pricing are subject to change without notice.
Please visit www.sjrhombus.com for the most current information.*